

Manufacturer:
KZWM OGNIОCHRON S.A.
ul. Krakowska 83c, 34-120 Andrychów, Poland
Phone +48 33 875 10 70, Fax +48 33 875 10 77
e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron
KZWM OGNIОCHRON S.A.

Application

Designed especially for protection of vans and trucks. Applied also in community buildings, office rooms, production facilities, storerooms, garages.



Basic features

- Easy and ergonomic operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Possibility of multiple refilling.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.


Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 97/23/EC.



Technical data

Extinguishing efficiency	13A 89B C
Weight of extinguishing agent	2 kg
Working agent	N ₂
Operation time	9 s
Cylinder test pressure	27 bar
Operation pressure	10 bar
Operating temperature	-30 °C / +60 °C
Total weight	3,5 kg
Fire under voltage	1000 V
Total height (A)	355 mm
Cylinder diameter (B)	110 mm



Powder extinguisher GP-2x ABC/PM

