

Smoke Alarm

MODEL: VST-S588

V-DSH-007C(A0)

DC Operated Photoelectric Smoke Alarm

FEATURES AND BENEFITS



- ▶ DC Operated Photoelectric Type Smoke Alarm
- ▶ Photoelectric Sensor For Slow Smoldering Fires
- ▶ Insects Proof
- ▶ Test button
- ▶ Non-radioactive technology for environmental friendly
- ▶ High and stable sensitivity
- ▶ With quick fix mounting bracket for easy installation
- ▶ Fitting and battery tamper-resist feature
- ▶ LED operation indicator
- ▶ Extra loud alarm sound over 85 dB
- ▶ Low-battery and battery missing warning indicator
- ▶ Auto-reset when smoke clears
- ▶ CE, BSI, SAI Global approved, comply with EN14604, AS3786 and UL217 standard

PRODUCT SPECIFICATIONS

Model Number	VST-S588
Detection Type	Photoelectric Chamber
Operation Temperature	5°C -45°C
Power Source	9 volt Battery
Standby Current	15uA max
Alarm Current	30mA max
Alarm Sound Level	85 decibels at 3 meters
Ambient Humidity	10%-90%
Sensitivity to Smoke	3.0-6.0 %Obs /m
Product Weight	167g

SHIPPING SPECIFICATIONS

Model Number	VST-S588
Unit Dimension	11.9cm x 11.9cm x 4.7 cm
Master Ctn. Quantity	100
Master Ctn. Dimension	62.5cm x 55cm x 27.5cm
Master Ctn. Weight	20 Kgs

Xiamen Vs-Top Electronics Co., Ltd.

2nd floor, No-107 Xiaguang Road, Haicang Xinyang Industrial District, Xiamen, China 361026

Tel: +86-592-6017700 Fax: +86-592-6017711

E-mail: sales@orientalert.com Website: www.orientalert.com

