

Smoke Detectors & Alarms



SSA-I/P-01



SSA-I/P-02



SSA-I/P-03



SSA-I/P-04



SSA-I/P-05



SSA-I/P-06



SSA-07



SSA-08

CE SGS Complied with EN14604

Model	SSA-I/P-01	SSA-I/P-02	SSA-I/P-03	SSA-I/P-04	SSA-I/P-05	SSA-I/P-06	SSA-07	SSA-08
Power Supply	DC 9V	DC 9V	DC 9V	DC 9V or AC~220V or Both DC9V&AC~220V			DC12V~24V	
Alarm Sound at 3 m	≥ 85 db	≥ 85 db	≥ 85 db	≥ 85 db	≥ 85 db	≥ 85 db	≥ 85 db	≥ 85 db
Static Current	< 8μA	< 8μA	< 8μA	< 8μA	< 8μA	< 8μA	< 8μA	< 8μA
Alarm Current	≤ 10mA	≤ 10mA	≤ 10mA	≤ 10mA	≤ 10mA	≤ 10mA	≤ 10mA	≤ 10mA
Working Humidity	≤ 93%RH	≤ 93%RH	≤ 93%RH	≤ 93%RH	≤ 93%RH	≤ 93%RH	≤ 93%RH	≤ 93%RH
Working Temperature	-5 ~ +40°C	-5 ~ +40°C	-5 ~ +40°C	-5 ~ +40°C	-5 ~ +40°C	-5 ~ +40°C	-5 ~ +40°C	-5 ~ +40°C
Low Voltage Alarm	5.5~6.2V	5.5~6.2V	5.5~6.2V	5.5~6.2V	5.5~6.2V	5.5~6.2V	5.5~6.2V	5.5~6.2V
Low Battery Alert	7~15 days	7~15 days	7~15 days	7~15 days	7~15 days	7~15 days	7~15 days	7~15 days
Size (mm)	Φ106 x 32	Φ106 x 46	Φ114 x 45	Φ126 x 41	Φ124 x 42	Φ124 x 49	Φ135 x 44	Φ98 x 52
Net Connection							✓	✓ (Only)
Guarantee	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years
Remark	I: Ionization smoke alarm, P: Photoelectric smoke alarm .							