



**Together:
We achieve more.**

Your local fire fighting expert ensures that you are safe in your home and can help you as an entrepreneur to protect your business processes optimally as they are a decisive competitive factor. As supplier we assist our partners in finding the best solution for you.

Quality made in Germany
Simple handling, high performance and a comprehensive product safety are essential for a successful fire fighting. Therefore we still focus on Made in Germany - a label that stands for absolute top quality.

Top ratings for more security
In addition, we offer many fire extinguishers with higher ratings. Top ratings provide additional extinguishing capacity, so they can be used even by the most unexperienced users without any training of fire fighting tactics, to actually get fire faster under control. Nevertheless your staff should be trained in using fire extinguishers to ensure a better performance. Ask your local fire fighting experts for assistance.

Environment in mind
Despite the demand for higher extinguishing performance, the environmental sustainability and disposal is one of the major issues of the 21st century. Therefore, in recognition of our

share of responsibility for the environment we have committed to reduce the share of fluorine in all foam extinguishers to the absolute minimum, even though we cannot entirely dispense with it in foam extinguishing agents for fire-protection technical reasons. Sparing use of paper, energy-conscious production and reduced use of packaging materials are a matter of course to us.

Jockel's Modular System pays off
All Jockel fire extinguishers within one product family are built nearly identically: device types of the same build considerably reduce spare parts demand. Many spare parts can be used in several devices.

At the same time, only a few maintenance tools are necessary. They can be used for several device types at once. For which reason Jockel devices are not only maintenance-friendly but particularly economic in maintenance.

Expect the Best
It is our passion to find the best solution for our customers. JOCKEL stands for flexible solutions, reliability, delivery on time and availability of all goods.

Mobile Extinguishers (excerpt only)

Information about our fire containers and other mobile extinguishers are available in our brochure.



Type	P 25 AJ P 50 AJ	P 50 GJ P 50 GJ BC P 50 GJ BCK P 75 J P 100 J	P 25 J Externa ABC P 50 J Externa ABC P 50 J Externa BC	S 50 JHW Bio Externa	S 50 J Bio S 50 FJ Bio	K 10 J K 20 J K 20 J with 2,5 m lance K 30 J KS 60 J ¹
Family	Mobile	Mobile	Mobile	Mobile	Mobile	Mobile
Agent	ABC-Powder	ABC-Powder BC-Powder BCK-Powder ABC-Powder ABC-Powder	ABC-Powder ABC-Powder BC-Powder	Bio-Foam	Bio-Foam	CO ₂
Mode of Function	Stored Pressure	Cartridge with external N ₂ -bottle	Cartridge with external CO ₂ -bottle	Cartridge with external CO ₂ -bottle	Cartridge with external N ₂ -bottle	Stored Pressure
Capacity	25 kg 50 kg	50 kg 50 kg 50 kg 75 kg 100 kg	25 kg 50 kg 50 kg	50 l	50 l 50 l	10 kg 20 kg 20 kg 30 kg 60 kg
Rating	A II B C A III B C	A IV B C III B C III B C A IV B C A IV B C	A II B C A III B C III B C	A IV B	A IV B	113 B 144 B 144 B 144 B 6 x 144 B
Working Pressure @ 20°C	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar
Temperature Range	-30°C to +60°C	-20°C to +60°C P 75/100J: -30°C to +60°C	-20°C to +60°C	+5°C to +60°C	+5°C to +60°C -20°C to +60°C	+5°C to +60°C
Discharge Time*/ Discharge Range*	58 sec. / 8 m 121 sec. / 8 m	65 sec. / 8 m 65 sec. / 8 m 65 sec. / 8 m 196 sec. / 8,5 m 261 sec. / 8,5 m	58 sec. / 8 m 121 sec. / 8 m 121 sec. / 8 m	180 sec. / 13 m discharge Height at least 9 m	115 sec. / 8 m 116 sec. / 8 m	15 sec. / 5 m 30 sec. / 5 m 30 sec. / 5 m 54 sec. / 5 m 63 sec. / 5 m
Height*/Width*	1050 mm / 450 mm 1042 mm / 580 mm	1025 mm / 620 mm 1025 mm / 620 mm 1025 mm / 620 mm	1050 mm / 450 mm 1050 mm / 450 mm 1050 mm / 450 mm	1110 mm / 440 mm	1025 mm / 620 mm 1025 mm / 620 mm	1240 mm / 940 mm 1240 mm / 940 mm 1240 mm / 940 mm 1640 mm / 940 mm 1640 mm / 940 mm
Weight*	49,0 kg 79,5 kg	97,5 kg 97,5 kg 97,5 kg 133 kg 158 kg	51,0 kg 82,5 kg 82,5 kg	90,0 kg	104,0 kg 104,0 kg	53,0 kg 74,0 kg 74,5 kg 94,0 kg 173,0 kg
Code <small>Bases need to be ordered separately.</small>	30-525-35 30-530-35	31-765-35 31-465-35 31-365-35 75-565-35 76-565-35	33-555-35 30-565-35 30-465-35	33-266-35	33-165-35 38-065-35	34-266-35 35-266-35 35-366-35 36-266-35 37-066-35

Subject to modifications and errors. Pictures can differ from actual products.

*Values could differ

¹approved according to DIN EN 3

Jockel-Promise

Good is never good enough. We are constantly working to improve our products and production processes so that we can meet the requirements of our customers successfully and make their lives safer. Made in Germany, a TÜV-certified quality assurance system, high-quality material and innovations are the key of our success.

Feuerschutz Jockel GmbH & Co. KG
Jägerwald 28-30 • D-42897 Remscheid
Telefon +49 2191.96 67 -0 • Fax +49 2191.96 67 -88
export@jockel.de • www.jockel.de

Jockel-Distributor



06/12



**Safety products for
your success**

Product overview

Other categories of products (excerpt only)

Extinguishing Systems	Fire Fighting Containers	Pressure boosting systems	RWA	Wall Hydrants	Smoke detector	Signs	First Aid	Fire Extinguisher Equipment	Tools & Spare Parts

Also ask for our new training extinguishers.



Type (Distribution Name)	PS 1 JM 8 PS 2 JM 13	PL 1 JM 8 P 2 LJM 13	PSF 1 LJ 8	SF 2 JM 5	F 2 JM 5	F 3 LJM 8	F 3 H System	P 6 LJKM 34 P 6 LJKM 43 P 6 LJKM 55 P 9 LJM 55 P 12 LJM 55	S 6 DJLM 21 S 6 LJM Bio 34 S 6 LJM Bio 43 S 9 DJLM 27 S 9 LJM Bio 43 S 9 LJM Bio 55	W 6 DJLM 8 WN 6 LJM 21 W 9 DJLM 21 WN 9 LJM 27	F 6 LJM 13	P 6 HK System 34 P 12 H System 55	SK 6 H System Bio 34 SK 9 H System Bio 43	W 6 H System 21 W 9 H System 27	P 6 JK 34 P 6 JK 43 P 6 JK 55 P 9 J 55 P 12 J 55	SN 6 J Bio 34 SN 6 J Bio 43 SN 9 J Bio 43 SN 9 J Bio 55	SK 6 J Bio 21 SK 6 J Bio 34 SK 9 J Bio 27 SK 9 J Bio 43	WN 6 J 21 W 6 J 27 WN 9 J 27 W 9 J 34	F 6 J 13 F 6 J Plus 13	K 2 J K 2 AJS K 5 J	P 6 JK Externa BC P 12 J Externa BC	P 12 MJ
Line	Mini	Mini	Mini	Mini	Mini	Mini	Mini/System	Standard	Standard	Standard	Standard	System	System	System	Classic / Universal	Classic / Universal	Classic / Universal	Classic / Universal	Classic / Universal	Industry	Industry	Industry
Agent	ABC Powder	ABC Powder	ABC Powder	Foam	Wet Chemical for Fat Fires	Wet Chemical for Fat Fires	Wet Chemical for Fat Fires	ABC Powder	Foam	Water with Additives	Wet Chemical for Fat Fires	ABC Powder	Foam	Water with Additives	ABC Powder	Foam	Foam	Water with Additives	Wet Chemical for Fat Fires	CO ₂	BC-Powder	Metal-Powder
Mode of Function	Stored Pressure	Stored Pressure	Stored Pressure	Stored Pressure	Stored Pressure	Stored Pressure	Cartridge	Stored Pressure	Stored Pressure	Stored Pressure	Stored Pressure	Cartridge	Cartridge/ Cartouche	Cartridge	Cartridge	Cartridge	Cartridge/ Cartouche	Cartridge	Cartridge	Stored Pressure	Cartridge	Cartridge
Capacity	1 kg 2 kg	1 kg 2 kg	1 kg	2 l	2 l	3 l	3 l	6 kg 6 kg 6 kg 9 kg 12 kg	6 l 6 l 6 l 9 l 9 l 9 l	6 l 9 l 9 l	6 l	6 kg 12 kg	6 l 9 l	6 l 9 l	6 kg 6 kg 6 kg 9 kg 12 kg	6 l 6 l 9 l 9 l	6 l 6 l 9 l 9 l	6 l 6 l 9 l 9 l	6 l	2 kg 2 kg 5 kg	6 kg 12 kg	12 kg
Rating	8 A 34 B C 13 A 89 B C	8 A 34 B C 13 A 89 B C	8 A 34 B C	5 A 55 B	5 A 34 B 40 F	8 A 55 B 75 F	8 A 55 B 75 F	34 A 233 B C 43 A 233 B C 55 A 233 B C 55 A 233 B C 55 A 233 B C	21 A 144 B 34 A 183 B 43 A 183 B 27 A 183 B 43 A 233 B 55 A 233 B	8 A 21 A 27 A	13 A 113 B 75 F	34 A 233 B C 55 A 233 B C	34 A 183 B 43 A 233 B	21 A 27 A	34 A 233 B C 43 A 233 B C 55 A 233 B C 55 A 233 B C	34 A 183 B 43 A 183 B 43 A 233 B 55 A 233 B	21 A 183 B 34 A 183 B 27 A 233 B 43 A 233 B	21 A 27 A 34 A	13 A 75 F 13 A 113 B 75 F	34 B 34 B 89 B	233 B C 233 B C	D
Working Pressure @ 20 °C	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar	60 bar	15 bar	15 bar
Temperature Range	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-20°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	+5°C to 60°C	+5°C to +60°C	+5°C to +60°C	-30° to +60°C	+0°C to + 60°C	+5°C bis + 60°C	-30°C to +60°C	+5°C to + 60°C	+5°C to + 60°C 0°C to +60°C +5°C to + 60°C 0°C to +60°C	+5°C to + 60°C -5°C to + 60°C	0°C to + 60°C -30°C to + 60°C	-30°C to +60°	-30°C to +60°	-20°C to +60°
Discharge Time/ Discharge Range*	7 sec. / 7 m 10 sec. / 9 m	8 sec. / 7 m 11 sec. / 9 m	9,5 sec. / 7 m	11 sec. / 6 m	14 sec. / 6 m	17 sec. / 7 m	17 sec. / 7 m	23 sec. / 8 m 23 sec. / 8 m 23 sec. / 8 m 22 sec. / 8 m 21 sec. / 8 m	47 sec. / 7 m 27 sec. / 7 m 27 sec. / 7 m 65 sec. / 8 m 41 sec. / 8 m 41 sec. / 8 m	35 sec. / 7 m 28 sec. / 8 m 46 sec. / 8 m 40 sec. / 8 m	39 sec. / 4 m	25 sec. / 8 m 34 sec. / 8 m	52 sec. / 7 m 54 sec. / 7 m	31 sec. / 7 m 44 sec. / 7 m	23 sec. / 8 m 23 sec. / 8 m 23 sec. / 8 m 26 sec. / 8 m 32 sec. / 9 m	23 sec. / 7 m 23 sec. / 7 m 37 sec. / 6 m 37 sec. / 7 m	33 sec. / 7 m 33 sec. / 7 m 44 sec. / 7 m 44 sec. / 7 m	25 sec. / 8 m 30 sec. / 8 m 38 sec. / 8 m 45 sec. / 8 m	26 sec. / 7 m 26 sec. / 7 m	7 sec. / 4m 10 sec. / 4 m 13 sec. / 5 m	27 sec. / 8 m 30 sec. / 8 m	23 sec. / -
Height*/Width*	268 mm / 120 mm 358 mm / 130 mm	300 mm / 135 mm 370 mm / 130 mm	236 mm / 110 mm	358 mm / 175 mm	370 mm / 145 mm	375 mm / 230 mm	375 mm / 230 mm	505 mm / 263 mm 505 mm / 263 mm 505 mm / 263 mm 546 mm / 270 mm 579 mm / 270 mm	592 mm / 240 mm 592 mm / 240 mm 592 mm / 240 mm 597 mm / 270 mm 597 mm / 270 mm 597 mm / 270 mm	592 mm / 240 mm 592 mm / 240 mm 597 mm / 270 mm 597 mm / 270 mm	592 mm / 240 mm	532 mm / 255 mm 684 mm / 260 mm	597 mm / 270 mm 599 mm / 268 mm	597 mm / 270 mm 599 mm / 268 mm	496 mm / 305 mm 496 mm / 305 mm 496 mm / 305 mm 522 mm / 275 mm 652 mm / 275 mm	560 mm / 280 mm 560 mm / 280 mm 560 mm / 290 mm 560 mm / 290 mm	560 mm / 280 mm 560 mm / 280 mm 560 mm / 290 mm 560 mm / 290 mm	560 mm / 280 mm 560 mm / 280 mm 560 mm / 290 mm 560 mm / 290 mm	560 mm / 280 mm 560 mm / 280 mm	470 mm / 270 mm 515 mm / 180 mm 705 mm / 490 mm	480 mm / 320 mm 629 mm / 345 mm	650 mm / 330 mm
Weight*	2,1 kg 3,6 kg	2,0 kg 3,5 kg	2,0 kg	3,8 kg	4,1 kg	6,5 kg	6,5 kg	9,4 kg 10,5 kg 9,4 kg 14,2 kg 17,7 kg	10,5 kg 10,5 kg 10,5 kg 14,4 kg 14,4 kg 14,4 kg	10,2 kg 10,2 kg 15,2 kg 15,2 kg	11,3 kg	10,3 kg 18,8 kg	10,6 kg 15,1 kg	10,6 kg 15,1 kg	10,3 kg 10,3 kg 10,3 kg 16,0 kg 19,0 kg	10,8 kg 10,8 kg 14,9 kg 15,4 kg	10,5 kg 10,5 kg 14,9 kg 14,9 kg	11,3 kg 12,0 kg 16,0 kg 17,0 kg	11,0 kg 11,0 kg	6,7 kg 5,1 kg 14,3 kg	11,6 kg 19,7 kg	19,1 kg
Code	14-501-35 24-501-35	14-581-35 21-581-35	bag included 14-557-35	25-011-35	25-301-35	32-301-35	32-378-35	60-201-35 66-150-35 60-101-35 62-101-35 90-501-35 70-501-35	66-180-35 66-150-35 66-401-35 98-181-35 96-150-35 96-401-35	60-081-35 60-001-35 90-081-35 90-001-35	60-319-35	61-278-35 71-578-35	69-185-35 99-185-35	65-030-35 95-030-35	Edition Classic 61-200-35 61-100-35 67-100-35 91-500-35 71-500-35	Edition Classic 69-100-35 68-400-35 99-100-35 98-400-35	Edition Classic 68-185-35 68-385-35 98-185-35 98-385-35	Edition Classic 65-230-35 65-200-35 95-230-35 95-200-35	Edition Classic 65-245-35 65-345-35	26-500-35 26-700-35 56-500-35	61-420-35 71-420-35	71-821-35

► Easy Fire Fighting

- Easy to handle
- Controllable discharge
- Evident safety pin to prevent extinguisher from being unintentionally triggered
- Suitable for electrical systems of up to 1,000 volts at a safety distance of 1 m

► Intelligent Design

- Compact and stable valve assembly
- High quality extinguishing agents
- Also available with high performance agents
- Mobile extinguishers from 3 l/kg with protective base
- Including weather-resistant brackets

► High Quality

- High quality steel container with a premium surface coating adding extra protection
- Compact and stable valve assembly
- Weather and UV-resistant individual parts

► Easy Service

- **Service-Friendly:** Easy refilling especially for cartridge extinguishers
- **Maintenance-Friendly:** Easy (dis)assembling parts
- **Economical:** Standardized spare parts; no special tools required

► Approvals

- According to EN 3 (national approvals for different countries)
- According to MED 96/98/EG

