

# TELEMASTER TELESCOPIC LADDER



Geprüft nach  
EN 1147



Approved according to EN 1147 "Portable ladder  
for fire-fighters"  
Certified by TÜV, TÜV GS-signed



 **rosenbauer**

**Essential advantages:**

- 2-person-rescue ladder according to EN 1147
- Certified by TÜV and TÜV-GS-signed
- Safety system (Hands and fingers are protected against injury when the ladder is slid together;

- Safety gap approx. 40 mm)
- Squeeze safety device
- Ideal for small and fast vehicles
- Small transportation dimensions (830 x 470 x 90 mm)
- Useful up to 3,5 m in all steps



The TELEMMASTER telescopic ladder is extremely simple to use. All rungs can be used at a maximum height of 3.50 m, however, the ladder can also be employed with any intermediate length.

**DATA:**

Number of rungs

11

**Dimensions and weight:**

Rung spacing

300 mm

Max. functional height

3500 mm

Intermediate height

up to 3500 mm

Transport length

830 mm

Weight

15 kg

Rung safety gap

40 mm

**Material:**

Inner slide and guide elements

POM plastic

Side frames / Treads

Al profile

Fastenings

Cast aluminium

**Order data:**

Order No.

80112801



Approved according to EN 1147



ROSENBAUER INTERNATIONAL Aktiengesellschaft  
A-4060 Leonding, Paschinger Str. 90, AUSTRIA

Tel.: +43 (0)70 6794-0  
Fax: +43 (0)70 6794-83  
E-Mail: office@rosenbauer.com  
<http://www.rosenbauer.com>

Text and illustrations are not binding. The illustrations may show optional extras only available at extra charge. ROSENBAUER retains the right to alter specifications and dimensions given herein without prior notice.