

Combined filling unit for Carbon Dioxide (CO<sub>2</sub>) and Nitrogen (N<sub>2</sub>) for small cartridges fire extinguishers and cylinders of all makes and sizes with the FRITZ EMDE universal filling rail.

**The unit is equipped with:**

- » digital scale (resolution 5 g) with automatic cut-off
- » Compressed-air driven CO<sub>2</sub>-pump
- » Compressed-air driven N<sub>2</sub>-pump
- » Filling speed regulator
- » Electrically relief valve
- » Universal FRITZ EMDE filling rail
- » CO<sub>2</sub>-filter
- » Safety valve (130 bar)

**Standard accessory:**

- » 3 adaptors for CO<sub>2</sub>-cartridges: 18 mm, 25 mm und 32 mm
- » 1 CO<sub>2</sub>-High-Pressure hose 2 m
- » 1 DF1-adaptor for filling of CO<sub>2</sub>-cylinders
- » 1 KS 5 support
- » 1 set of socket wrenches, 10 – 32 mm
- » 1 CO<sub>2</sub>-steel filter

KUD6-DI-N<sub>2</sub> PROTECT (No. 263 000)



## TECHNICAL DATA

Filling capacity CO <sub>2</sub> :	max. 5 kg/min
Working pressure:	max. 130 bar
Safety valve:	130 bar
Motor:	230 V, 10 A, 50 Hz
Dimension (l x w x h):	approx. 1300 x 750 x 1250 mm
Working height:	850mm
Colour:	hammer finish painted blue

**Accessories available at extra charge:**

- » Floor scale with automatic cut-off 200 kg, 20 g resolution display integrated in filling unit scale platform approx. 600 x 400 mm incl. cylinder bracket
- » CO<sub>2</sub>-QUICK fast filling adaptor
- » Raisable safety guard for filling rail
- » Label printer

