

CODE: MBK24-250HGEL-LTH

ERP: 0501163

Trolley Fire Extinguisher 25L HGEL Special Type



CHARACTERISTICS

Suppression Agent Type	Agent for Li-on Batteries
Approval Type	CE, MED, MIRTEC
Extinguisher Type	Trolley
Capacity	25
Extinguishing Agent	HydroGel BM 048
Operating Temperature	+5~+60 °C
Max Allowable Pressure	18 bar
Test Pressure	28 bar
Volume of Equipment	30±1 L
Cylinder Height	724±5 mm
Cylinder Diameter	254±2 mm
Cylinder Neck Thread	G2x11
Cylinder Material	HP295
Valve Material	HPb59-1
Safety Valve	22~28 bar
Approx. gross Weight	65 kg
Approx. Dimensions	1020x464x579 mm
Paint Finish	RAL3000



Issue Date: 21/02/2025

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P¹ str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com