

UNISEK® 4.0

Technical details:

- made of high-resistant aluminium alloy
- special surface coating – wear-resistant
- transferable torque of 500 Nm
- weight of 1200 g
- all parts replaceable
- LED-lamp is exchangeable / batteries are easy renewable
- safety click into place of folding mechanism, saw and socket connection
- the rescue tool is ready for service within seconds and, with its fold-up and extension capabilities, it can be ideally adapted to the circumstances prevailing
- length: 250 mm folded, 490 mm unfolded incl. UNI-combined grip
- width: 30 mm

Contact:

UHLIG Präzisions Fertigungs GmbH
Straße der Befreiung 12a
D-09423 Gelenau

Tel.: 0049 (0)37297 / 49892
Fax: 0049 (0)37297 / 49883
Internet: www.UNISEK.de
Email: info@UNISEK.de

Copyright 09/2005

All rights reserved!
Subject to change without notice!

Made in Germany

Layout and printing: Annaberger Druckzentrum GmbH
Gewerbering 10, D-09456 Annaberg-Buchholz



leather holster with two detachable loops for attaching to a safety belt or hip belt



all functions are available when wearing gloves



An engraving of names is possible

Optionally additions to holster of UNISEK® 4.0:
Belt system to sling tool or additionally fastening point,
set composed of tape sling 1.2 m and
2 HMS aluminium karabiner

UNISEK® 4.0

Universal tool for special task forces

- patented -



**Always ready for service,
Any place,
Any time!**

UNI-combined grip

Optimize the leverage or used as single tool



Key for triangular lock mechanisms by DIN 3223 e.g. down comer hydrant, bollards, barriers



Connecting all Storz-couplings size A / B / C / D and DN 32 / DN 50 for hazardous goods



Wrench with key width 7+8+11 mm e.g. usage on wall hydrant or gas tap etc. if the hand wheel is missing



UNI-lever
All-round tool, always there,, always useable.



Conical square key as spare for windows and door locks



Key for electric / switch cubicles



Key for emergency locking / de-locking of lifts



Impact mandrel for single-pane safety glass



Servicing the spindle of the above-ground hydrant



Glass saw for easy cut out of multi-layer safety glass

LED-lamp - integrated usage - substid checking of vital functions - ascertaining route or orientation



square key for train doors / windows etc.



Belt cutter



Opening / closing of hydrant closure covers (cover capsule) by DIN 3223

Lever tip, breaker tool, elongated by UNI-combined grip - up to 500 Nm - support points for controlled force transmission - easy entering and widening of gabs, to lift or break open Example: Opening of doors / Opening of gates

