# **DeckMaster**<sup>™</sup>

## **DeckMaster Monitor**

The DeckMaster Monitor is a technologically advanced, electrically controlled deck monitor with automated elevating capability. The unique design of the DeckMaster Monitor allows electric elevation and positioning 26" above the base of the flange for operation over obstructions with the push of a switch.

Style 3440 Shown deployed with Style 1577 SaberMaster<sup>™</sup> Nozzle

26

Apparatus

Deck

Style 3440

Shown in a

typical stowed position

#### 3440 DeckMaster Electric Monitor

- 340° horizontal rotation with adjustable stops
- Vertical travel 90° above to 45° below horizontal
- Manual override for horizontal, vertical and elevation control
- Stow position set easily by the end user
- Automatic drain for freeze protection
- Diagnostic light for trouble-shooting
- Connection for deployed indicator light
- Available in 12 or 24 volt Must specify
- Obstacle avoidance available Must specify
- See page 167 for Monitor/Fog Nozzle Compatibility Chart

See page 45 for Electric Monitor Accessories

Style	Weight lbs. (kg)	In Stowed Position			Inlet	Outlet	Flow	
		Height	Width	Depth	Intet	Outlet	GPM	LPM
3440	55 (25 kg)	14 <sup>1</sup> /2" (368 mm)	16 ³⁄4" (425 mm)	17" (431 mm)	3" FL (75 mm)	2 <sup>1</sup> /2" NH (65 mm)	1250	4800





#### Combine with the new SaberMaster nozzle to meet new NFPA 1901 recommendations to use remote control monitors for safe deck gun operations.

Remote DeckMaster operation eliminates the need to have a firefighter on the deck to operate the monitor.



DeckMaster available with position feedback for position indicator option

## Electric Riser for DeckMaster & StreamMaster™

Overcome increased heights of apparatus bodies, raised roof cabs, and other obstacles with the electric riser. It enables an added 12-inches of extension and is the perfect complement to the already superior versatility of the DeckMaster or StreamMaster monitors.

#### 3406 Electric Riser For DeckMaster & StreamMaster

- 3" waterway
- 12" extension
- $\bullet$  With unique three-piece design, the extremely compact device is only 17  $^{1\!\!\!/}_{4}$  when nested
- Can be utilized within pump modules that have limited space
- Electrically actuated (12 or 24 volt)
- Durable lightweight Pyrolite® construction
- Manual override
- 5 year warranty
- Inlet option: 3" victaulic or NPT (Must specify)
- outlet options 3" or 4" flange (Must specify)



17 <sup>1</sup>/4"

Electric Riser shown in extended position with Style 3440 DeckMaster and Style 5075 Akromatic 1250 Nozzle